



BLUE 75™ THREAD SEALANT

BLU-2-0200

Formulated, Designed & Tested for Plastic Piping Products



While many thread sealants and pipe joint compounds claim to be suitable for use with plastics, several have been found to produce stress cracking due to chemical incompatibility. Improper application of Teflon® tape sealants can result in over-stressed threaded connections and potential joint failures. Research has proven Spears® BLUE 75™ thread sealant to be the superior choice for reliable joint make-up of all Spears® thermoplastic piping products.

Non-Hardening, Lubricating Anti-Seize Formulation

Spears® BLUE 75™ is a special formulation which remains crushable to -50°F. Partial containers remain usable for years when properly stored. Wipes clean from hands or tools with a dry rag for up to 15 minutes after application. Anti-seize properties allow easy assembly and positive seal without over tightening.

Safe, nontoxic, Lead & Silicon Free

Spears® BLUE 75™ is NSF tested and Certified safe for use with potable water. Will not transfer taste or odor to the sealed system.

Non-Corrosive, Non-Conductive

Promotes the advantages found with the use of thermoplastic piping components for a broad range of applications, easy maintenance and long system life.

Convenient Packaging Availability

Spears® BLUE 75™ is available in 1/4 pint, 1/2 pint, 1 pint and 1 quart metal cans with brush top applicators.

Specially Designed for Spears® Threaded Fittings & Valves

Spears® BLUE 75™ is recommended for use with all Spears® thermoplastic piping system components, including PVC and CPVC products, CPVC fire sprinkler products, CPVC CTS (Copper-Tube-Size) products, and Spears® plastic-to-metal transition products.

Suitable for Sealing Threads in Metal, ABS, PVC, CPVC & Nylon Piping Systems

While specially designed for Spears® products, Spears® 75™ is suitable for use in metal and plastic systems properly designed for handling a wide variety of liquids and gases (not recommended for use in oxygen handling systems).

Basic Specifications

Color	Light Blue
Consistency	Grit-Free, crushable paste
Potable Water Approval	National Sanitation Foundation (NSF)
U.S. Federal Specifications	Meets and exceeds TT-5-1732
Shelf Life	Indefinite when properly stored in closed container



PROGRESSIVE PRODUCTS FROM SPEARS® INNOVATION & TECHNOLOGY

Visit our web site: www.spearsmfg.com

General Instructions

Store and apply between 20°F (-7°C) and 140°F (60°C): remains crushable to -50°F (-45°C). Stir before using.

1. Threads should be properly formed or cut with a good die and free of all oils, dirt, moisture, etc.
2. Apply Spears® BLUE75™ freely to male threads with brush applicator. Brush well into threads to ensure a leak-free joint.
3. Assemble joint in usual manner. Take care not to over tighten. System may be placed into service immediately.

Caution: Do not take internally.
Do not burn - fumes may be harmful.
Wash hands and exposed areas after handling.

FIRST AID

Eyes: Flush 15 minutes with clean water.

Skin: Wash with soap and water.

Ingestion: Only if conscious, give large amounts of water and induce vomiting. Obtain medical attention.

User shall determine the suitability of the product for its intended use and all risk and liability in connection therein. Manufacturer is not responsible for consequential damages.



SPEARS® MANUFACTURING COMPANY • CORPORATE OFFICE

15853 Olden St., Sylmar, CA 91342 • PO Box 9203, Sylmar, CA 91392

(818) 364-1611 • www.spearsmfg.com



PACIFIC SOUTHWEST

15860 Olden St.
Sylmar (Los Angeles), CA 91342
(818) 364-1611 • (800) 862-1499
Fax (818) 367-3014

ROCKY MOUNTAIN

4880 Florence St.
Denver, CO 80238
(303) 371-9430 • (800) 777-4154
Fax (303) 375-9546

UTAH

1641 South 700 West
Salt Lake City, UT 84104
(801) 972-0659
Fax (801) 972-0688

SOUTHEAST

4205 Newpoint Pl. Suite 100
Lawrenceville (Atlanta), GA 30043
(678) 985-1263 • (800) 662-6326
Fax (678) 985-5642

MIDWEST

1 Gateway Ct. Suite A
Bolingbrook (Chicago), IL 60440
(630) 759-7529 • (800) 662-6330
Fax (630) 759-7515

NORTHWEST

4103 C St. NE Suite 200
Auburn (Seattle), WA 98002
(253) 939-4433 • (800) 347-7327
Fax (253) 939-7557

SOUTH CENTRAL

4250 Patriot Dr. Suite 300
Grapevine (Dallas), TX 76051-2317
(972) 691-4003 • (800) 441-1437
Fax (972) 691-4404

NORTHEAST

590 Industrial Dr. Suite 100
Lewisberry (Harrisburg), PA 17339-9532
(717) 938-8844 • (800) 233-0275
Fax (717) 938-6547

FLORIDA

3445 Bartlett Blvd.
Orlando, FL 32811
(407) 843-1960 • (800) 327-6390
Fax (407) 425-3563

INTERNATIONAL SALES

15853 Olden St.
Sylmar (Los Angeles), CA 91342
(818) 364-1611 • Fax (818) 898-3774
E-mail: export@spearsmfg.com