



Schedule 40 Fittings & Accessories
True Union 2000 Standard Ball Valve - PVC White & True Union 2000 Standard Ball Valves

True Union 2000 Standard Ball Valve - PVC White

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

PVC White True Union 2000 Standard Ball Valve



Socket Ends - EPDM O-rings

Pressure Rating @73° F (23° C) = 235 psi
 Maximum Service Pressure = 140° F (60° C)
 Temperature/Pressure De-ratings Apply

3622-015W	1-1/2	1	8	608	93.35
3622-020W	2	1	8	608	123.18

Check with Spears® for additional size availability

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

PVC White True Union 2000 Standard Ball Valves



SR Threaded Ends - EPDM O-rings

Pressure Rating @73° F (23° C) = 235 psi
 Maximum Service Pressure = 140° F (60° C)
 Temperature/Pressure De-ratings Apply

3621-015WSR	1-1/2	1	8	608	99.98
3621-020WSR	2	1	8	608	130.35

Check with Spears® for additional size availability

True Union 2000 Standard Ball Valves



Socket Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" = 235 psi
 2-1/2" - 4" = 150 psi
 Flanged = 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)

Temperature/Pressure De-ratings Apply
 All Valves Assembled with Silicone-Free, Water Soluble Lubricant
 See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

PVC Standard

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
------	------	-----	--------	---------	-----------

Socket & Threaded Ends

1/2	3629-005 39.77	3639-005 44.23	1	18	608
3/4	3629-007 47.03	3639-007 52.32	1	18	608
1	3629-010 56.02	3639-010 62.40	1	12	608
1-1/4	3629-012 77.48	3639-012 98.91	1	8	608
1-1/2	3629-015 93.35	3639-015 103.62	1	8	608
2	3629-020 123.18	3639-020 135.62	1	4	608

Socket Ends

2-1/2	3622-025 235.95	3632-025 320.80	1	0	609
3	3622-030 312.14	3632-030 346.81	1	0	609
4	3622-040 527.23	3632-040 586.01	1	0	609

Threaded Ends

2-1/2	3621-025 235.95	3631-025 320.80	1	0	609
3	3621-030 312.14	3631-030 346.81	1	0	609
4	3621-040 527.23	3631-040 586.01	1	0	609

SR Threaded Ends

1/2	3621-005SR 40.63	3631-005SR 45.08	1	18	608
3/4	3621-007SR 49.06	3631-007SR 54.39	1	18	608
1	3621-010SR 58.06	3631-010SR 64.44	1	18	608
1-1/4	3621-012SR 83.67	3631-012SR 105.08	1	12	608
1-1/2	3621-015SR 99.98	3631-015SR 110.24	1	8	608
2	3621-020SR 130.35	3631-020SR 142.81	1	8	608

PVC Standard (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
------	------	-----	--------	---------	-----------

SR Threaded Ends

2-1/2	3621-025SR 256.11	3631-025SR 340.14	1	0	609
3	3621-030SR 331.52	3631-030SR 366.17	1	0	609
4	3621-040SR 550.00	3631-040SR 608.60	1	0	609

Spigot Ends

1/2	3627-005 39.77	3637-005 44.23	1	18	608
3/4	3627-007 47.03	3637-007 52.32	1	18	608
1	3627-010 56.02	3637-010 62.40	1	12	608
1-1/4	3627-012 77.48	3637-012 98.91	1	12	608
1-1/2	3627-015 93.35	3637-015 103.62	1	8	608
2	3627-020 123.18	3637-020 135.62	1	8	608
2-1/2	3627-025 236.74	3637-025 320.80	1	0	609
3	3627-030 312.14	3637-030 346.81	1	0	609
4	3627-040 527.23	3637-040 586.01	1	0	609

Flanged Ends

1/2	3623-005 56.87	3633-005 60.65	1	8	608
3/4	3623-007 72.05	3633-007 78.36	1	8	608
1	3623-010 87.18	3633-010 93.75	1	8	608
1-1/4	3623-012 102.35	3633-012 113.76	1	4	608
1-1/2	3623-015 128.93	3633-015 140.29	1	4	608
2	3623-020 205.28	3633-020 217.74	1	0	608

Schedule 40 Fittings & Accessories
True Union 2000 Standard Ball Valves



PVC Standard (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
-------------	------	-----	-----------	------------	--------------

Flanged Ends

2-1/2	3623-025 379.14	3633-025 385.41	1	0	609
3	3623-030 392.87	3633-030 520.28	1	0	609
4	3623-040 842.57	3633-040 976.66	1	0	609



Schedule 40 Fittings & Accessories CWV Ball Valves & Utility Ball Valves

CWV Ball Valves



**A Combination of Economy & Quality - Made in the U.S.A.
For Greater Value in a General Purpose Cold Water Valve**

Pressure Rating @ 73°F (23°C), Water = 125 psi

You don't have to go overseas to find an economical general purpose ball valve! Spears® CWV BALL VALVES are produced in the U.S.A. with Spears® high quality construction and NSF® Certified for potable water service. Designed for use with cold water, these PVC valves may be suitable for some applications previously handled by Spears® Utility Valves. Available in IPS sizes 1/2" through 2" with a Full 1-Year Warranty.

CWV PVC Ball Valve

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
Socket Ends					
8722-005	1/2	50	0	204	8.43
8722-007	3/4	25	0	204	10.00
8722-010	1	25	0	204	13.60
8722-012	1-1/4	20	0	204	18.03
8722-015	1-1/2	20	0	204	27.52
8722-020	2	10	0	204	34.78

CWV PVC Ball Valve

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
Threaded Ends					
8721-005	1/2	50	0	204	10.41
8721-007	3/4	25	0	204	12.35
8721-010	1	25	0	204	16.80
8721-012	1-1/4	20	0	204	22.25
8721-015	1-1/2	20	0	204	33.97
8721-020	2	10	0	204	42.94

Utility Ball Valves



Pressure Rating @ 73°F (23°C), Water
1/2" - 6"
150 psi
Maximum Service Temperature
PVC = 140°F (60°C)
Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free,
Water Soluble Lubricant

PVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Disc Code
PVC White					
1/2	2621-005 9.37	2622-005 9.37	50	0	215
3/4	2621-007 11.12	2622-007 11.12	25	0	215
1	2621-010 15.12	2622-010 15.12	25	0	215
1-1/4	2621-012 20.03	2622-012 20.03	20	0	215
1-1/2	2621-015 30.57	2622-015 30.57	20	0	215
2	2621-020 38.64	2622-020 38.64	8	0	215
2-1/2	2621-025 66.14	2622-025 66.14	6	0	214
3	2621-030 118.62	2622-030 118.62	1	4	214
4	2621-040 217.41	2622-040 217.41	1	0	214
6 (Lever Handle)	---	2622-060 350.76	1	0	214
PVC Gray					
1/2	2621-005G 9.37	2622-005G 9.37	50	0	215

PVC w/EPDM O-ring Seal (continued)

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Disc Code
PVC Gray					
3/4	2621-007G 11.12	2622-007G 11.12	25	0	215
1	2621-010G 15.12	2622-010G 15.12	25	0	215
1-1/4	2621-012G 20.03	2622-012G 20.03	20	0	215
1-1/2	2621-015G 30.57	2622-015G 30.57	20	0	215
2	2621-020G 38.64	2622-020G 38.64	8	0	215
2-1/2	2621-025G 66.14	2622-025G 66.14	6	0	214
3	2621-030G 118.62	2622-030G 118.62	1	4	214
4	2621-040G 217.41	2622-040G 217.41	1	0	214

Schedule 40 Fittings & Accessories Single Entry Ball Valves



PVC White – Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 3" - 4" 150 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 Temperature/Pressure De-ratings Apply
 Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant.
 See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

PVC White

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005W 19.02	2421-005W 21.09	2431-005W 23.46	10	120	240
3/4	2411-007W 25.75	2421-007W 26.55	2431-007W 29.51	10	80	240
1	2411-010W 28.11	2421-010W 31.22	2431-010W 34.72	10	0	240
1-1/4	2411-012W 39.08	2421-012W 43.46	2431-012W 48.28	6	0	240
1-1/2	2411-015W 50.66	2421-015W 58.82	2431-015W 63.78	5	0	240
2	2411-020W 57.03	2421-020W 63.31	2431-020W 70.37	5	0	240
3	2411-030W 207.42	2421-030W 257.32	2431-030W 296.68	1	0	240
4	2411-040W 438.47	2421-040W 483.08	2431-040W 525.14	1	0	240

Socket Ends

1/2	2412-005W 19.02	2422-005W 21.09	2432-005W 23.46	10	120	240
3/4	2412-007W 25.75	2422-007W 26.55	2432-007W 29.51	10	80	240
1	2412-010W 28.11	2422-010W 31.22	2432-010W 34.72	10	0	240
1-1/4	2412-012W 39.08	2422-012W 43.46	2432-012W 48.28	6	0	240
1-1/2	2412-015W 50.66	2422-015W 58.82	2432-015W 63.79	5	0	240
2	2412-020W 57.03	2422-020W 63.31	2432-020W 70.37	5	0	240
3	2412-030W 207.42	2422-030W 257.32	2432-030W 296.68	1	0	240
4	2412-040W 438.47	2422-040W 483.08	2432-040W 525.14	1	0	240



Schedule 40 Fittings & Accessories
Electro Actuated True Union 2000 Standard Ball Valve & Electro Actuated Compact 2000 Ball Valve



General Purpose True Union design, 1/4-turn shutoff. Basic On-Off operation.

- Blocked Seal Carrier
- PTFE/HDPE Seats
- 235 psi @ 73°F (23°C) (flanged 150 psi)
- 115 VAC standard, optional voltages available
- High Impact PP NEMA 4x Enclosure, SS316 Fasteners
- 2-Position with Stem-mounted Visual Open/Close Indicator

See **Electric Actuator Accessories** for "2-wire" Control Add-on Actuator Accessory

PVC Electro Actuated True Union 2000 Standard Ball Valve

O-ring Joint	EPDM			FKM			Disc Code
	Socket & Thread	SR Thread	Flanged	Socket & Thread	SR Thread	Flanged	
Size	Part # Price Each	Part # Price Each	Part # Price Each	Part # Price Each	Part # Price Each	Part # Price Each	
1/2	E1453-005 469.73	E1451-005SR 470.59	E1457-005 577.91	E1454-005 517.58	E1452-005SR 518.55	E1458-005 636.74	500
3/4	E1453-007 479.98	E1451-007SR 481.93	E1457-007 606.21	E1454-007 536.13	E1452-007SR 538.09	E1458-007 675.55	500
1	E1453-010 494.41	E1451-010SR 494.41	E1457-010 632.88	E1454-010 548.11	E1452-010SR 550.23	E1458-010 701.72	500
1-1/4	E1553-012 506.39	E1551-012SR 512.47	E1557-012 658.42	E1554-012 584.32	E1552-012SR 590.29	E1558-012 759.53	500
1-1/2	E1553-015 535.73	E1551-015SR 542.20	E1557-015 691.06	E1554-015 599.61	E1552-015SR 606.21	E1558-015 773.62	500
2	E1553-020 567.65	E1551-020SR 574.68	E1557-020 760.69	E1554-020 631.15	E1552-020SR 637.77	E1558-020 845.79	500



General purpose industrial grade sealed unit design, 1/4-turn shutoff. Basic On-Off operation.

- Maintenance-free
- PTFE Seats
- 235 psi @ 73°F (23°C) (flanged 150 psi)
- 115 VAC standard, optional voltages available
- High Impact PP NEMA 4x Enclosure, SS316 Fasteners
- 2-Position with Stem-mounted Visual Open/Close Indicator

See **Electric Actuator Accessories** for "2-wire" Control Add-on Actuator Accessory

PVC Electro Actuated Compact 2000 Ball Valve

O-ring Joint	EPDM			FKM			Disc Code
	Socket	Thread	Flanged	Socket	Thread	Flanged	
Size	Part # Price Each	Part # Price Each	Part # Price Each	Part # Price Each	Part # Price Each	Part # Price Each	
1/2	E1404-005 452.61	E1406-005 452.61	E1408-005 557.42	E1405-005 498.81	E1407-005 498.81	E1409-005 587.83	496
3/4	E1404-007 463.71	E1406-007 463.71	E1408-007 586.16	E1405-007 515.36	E1407-007 515.36	E1409-007 616.72	496
1	E1404-010 472.03	E1406-010 472.03	E1408-010 604.24	E1405-010 523.54	E1407-010 523.54	E1409-010 635.27	496
1-1/4	E1504-012 488.69	E1506-012 488.69	E1508-012 636.49	E1505-012 552.26	E1507-012 552.26	E1509-012 670.07	496
1-1/2	E1504-015 502.61	E1506-015 502.61	E1508-015 648.42	E1505-015 563.01	E1507-015 563.01	E1509-015 686.42	496
2	E1504-020 524.78	E1506-020 524.78	E1508-020 705.54	E1505-020 585.32	E1507-020 585.32	E1509-020 744.75	496