



Globe Valves



Pressure Rating @ 73°F (23°C), Water
2-1/2" - 6" 150 psi
Maximum Service Temperature
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply
All Valves Assembled with Silicone-Free,
Water Soluble Lubricant
Suitable for Vacuum Service

Internal Repair Kit includes 1-Bonnet O-ring along with a factory assembled (required) internal component replacement unit consisting of Bonnet assembled with Stem/O-rings, Seat & Seal Carrier components. Install in valve using existing valve Bolts/Nuts/Washers, and Handle/Nut.

CPVC Flanged Ends

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
2-1/2	6023-025C 976.00	6033-025C 1025.04	1	0	622
3	6023-030C 1024.57	6033-030C 1138.97	1	0	622
4	6023-040C 1330.67	6033-040C 1462.78	1	0	622
6	6023-060C 2071.91	6033-060C 2089.43	1	0	622

CPVC Internal Repair Kits

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
2-1/2	GL-ERK-025C 689.17	GL-VRK-025C 765.76	1	0	299
3	GL-ERK-030C 788.38	GL-VRK-030C 865.75	1	0	299
4	GL-ERK-040C 893.94	GL-VRK-040C 983.81	1	0	299
6	GL-ERK-060C 1276.81	GL-VRK-060C 1404.99	1	0	299

Needle Valves



Pressure Rating @ 73°F (23°C), Water
CPVC 235 psi
Maximum Service Temperature
CPVC = 200°F (82°C)
Solid PTFE Stem Seals
No Elastomer or Lubricants used
Valves include Panel Mounting Nut

CPVC Needle Valve

Size	Threaded	Socket	SR Threaded	Std Pk	Mstr Pk	Disc Code
------	----------	--------	-------------	--------	---------	-----------

Globe Pattern

1/4	5591-002C 83.94	5592-002C 83.94	---	1	18	219
3/8	5591-003C 83.94	5592-003C 83.94	---	1	18	219
1/2	5591-005C 88.77	5592-005C 88.77	5591-005CSR 91.04	1	18	219

Angle Pattern

1/4	5691-002C 83.94	5692-002C 83.94	---	1	18	219
3/8	5691-003C 83.94	5692-003C 83.94	---	1	18	219
1/2	5691-005C 88.77	5692-005C 88.77	5691-005CSR 91.04	1	18	219