



## Polypropylene Fittings & Accessories Industrial Swing Check Valves



Threaded Bonnet on Sizes 3/4", 1" & 1-1/4"

Pressure Rating @ 73°F (23°C), Water  
 3/4" - 4" 150 psi  
 6" 100 psi  
 8" 70 psi

Maximum Service Temperature  
 PP = 180°F (82°C)  
 Temperature/Pressure De-ratings Apply  
 All Valves Assembled with Silicone-Free Lubricants



Bolted Bonnet on Sizes 1-1/2" & Up

**General Installation Information:** Swing check valves are designed for horizontal installations, but may be installed in up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec.

### Industrial Swing Check Valves

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
<b>PP</b>					
<b>3/4</b>	4423-007P <b>563.29</b>	4433-007P <b>625.86</b>	1	12	113
<b>1</b>	4423-010P <b>673.87</b>	4433-010P <b>734.44</b>	1	4	113
<b>1-1/4</b>	4423-012P <b>807.65</b>	4433-012P <b>897.31</b>	1	0	113
<b>1-1/2</b>	4423-015P <b>1002.77</b>	4433-015P <b>1091.16</b>	1	0	113
<b>2</b>	4423-020P <b>1072.15</b>	4433-020P <b>1204.66</b>	1	0	113
<b>2-1/2</b>	4423-025P <b>1785.13</b>	4433-025P <b>1985.68</b>	1	0	112
<b>3</b>	4423-030P <b>1876.73</b>	4433-030P <b>2244.16</b>	1	0	112
<b>4</b>	4423-040P <b>2552.76</b>	4433-040P <b>2833.55</b>	1	0	112
<b>6</b>	4423-060P <b>4835.67</b>	4433-060P <b>5377.21</b>	1	0	112
<b>8</b>	4423-080P <b>9256.18</b>	4433-080P <b>10171.67</b>	1	0	112

### Swing Check Valve With Counter Balance (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
<b>PP</b>					
<b>1-1/4</b>	4423CB-012P <b>880.14</b>	4433CB-012P <b>1354.36</b>	1	0	113
<b>1-1/2</b>	4423CB-015P <b>1244.07</b>	4433CB-015P <b>1670.49</b>	1	0	113
<b>2</b>	4423CB-020P <b>1340.19</b>	4433CB-020P <b>1505.82</b>	1	0	113
<b>2-1/2</b>	4423CB-025P <b>2069.04</b>	4433CB-025P <b>2541.67</b>	1	0	112
<b>3</b>	4423CB-030P <b>2517.42</b>	4433CB-030P <b>3149.68</b>	1	0	112
<b>4</b>	4423CB-040P <b>2882.82</b>	4433CB-040P <b>3167.00</b>	1	0	112
<b>6</b>	4423CB-060P <b>5363.56</b>	4433CB-060P <b>6882.82</b>	1	0	112
<b>8</b>	4423CB-080P <b>9791.67</b>	4433CB-080P <b>10707.18</b>	1	0	112

### Swing Check Valve With Arrow Indicator

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
<b>PP</b>					
<b>3/4</b>	4423I-007P <b>571.34</b>	4433I-007P <b>633.92</b>	1	12	113
<b>1</b>	4423I-010P <b>685.14</b>	4433I-010P <b>790.82</b>	1	4	113
<b>1-1/4</b>	4423I-012P <b>880.14</b>	4433I-012P <b>976.99</b>	1	0	113
<b>1-1/2</b>	4423I-015P <b>1131.42</b>	4433I-015P <b>976.99</b>	1	0	113
<b>2</b>	4423I-020P <b>1101.74</b>	4433I-020P <b>1249.35</b>	1	0	113
<b>2-1/2</b>	4423I-025P <b>1795.51</b>	4433I-025P <b>2012.18</b>	1	0	112
<b>3</b>	4423I-030P <b>2237.73</b>	4433I-030P <b>2335.62</b>	1	0	112
<b>4</b>	4423I-040P <b>2563.15</b>	4433I-040P <b>2843.98</b>	1	0	112
<b>6</b>	4423I-060P <b>4940.04</b>	4433I-060P <b>5422.53</b>	1	0	112
<b>8</b>	4423I-080P <b>9325.12</b>	4433I-080P <b>10274.48</b>	1	0	112

### Swing Check Valve With Counter Balance

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
<b>PP</b>					
<b>3/4</b>	4423CB-007P <b>721.01</b>	4433CB-007P <b>801.11</b>	1	12	113
<b>1</b>	4423CB-010P <b>862.53</b>	4433CB-010P <b>940.06</b>	1	4	113