

**CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves & Pipe**



PRODUCT INFORMATION

APPLICATION

Spears® Copper Tube Size (CTS) fittings are manufactured from chlorinated polyvinyl chloride (CPVC) for use with SDR-11 piping systems of CTS outside diameter in hot and cold water distribution systems. Check state and local codes for application and restrictions.

CONFORMANCE STANDARDS

Spears® CPVC CTS fittings conform to ASTM D 2846 Specification for Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Hot and Cold Water Distribution Systems.

WORKING PRESSURE

Spears® CPVC CTS fittings have a continuous working pressure rating of 100 psi at 180°F (82°C) [400 psi at 73°F (23°C)].

PRODUCT CERTIFICATION

Spears® CPVC CTS fittings and Special Reinforced (SR) Thread transition adapters are tested and certified by the National Sanitation Foundation (NSF®) to ASTM D 2846 for use in Hot and Cold Water Distribution Systems, and for safe use in potable water systems under NSF® Standard 14/61.


TESTING

Once the system has been installed and allowed to cure properly, the system shall be tested in accordance with applicable code requirements. When testing with water (hydrostatic testing), the system must be slowly filled with water and the air bled from the highest and furthest points in the system before test pressure is applied. Failure to do so can cause damage to the piping system and could be harmful to the job site personnel should a failure occur. If a leak is found, the affected product must be cut out and discarded. A new section can be installed using couplings or other approved means.

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

TEE

Socket x Socket x Socket



4101-005	1/2	25	300	035	1.56
4101-007	3/4	25	200	035	2.92
4101-010	1	10	120	035	15.31
4101-012	1-1/4	10	80	035	23.48
4101-015	1-1/2	5	60	035	30.59
4101-020	2	5	0	035	49.45

DROP EAR TEE (Fitting with Bracket)

Socket x Socket x Socket



DE4101-005	1/2	25	150	035	3.32
------------	-----	----	-----	-----	------

DROP EAR BRACKET ONLY

For 4101-005 and 4106-005



DES-005	1/2	800	0	035	6.17
---------	-----	-----	---	-----	------

REDUCING TEE

Socket x Socket x Socket



4101-074	1/2X1/2X3/4	25	300	035	5.42
4101-094	3/4X1/2X1/2	25	300	035	2.91
4101-095	3/4X1/2X3/4	25	300	035	2.91
4101-101	3/4X3/4X1/2	25	300	035	3.01
4101-102	3/4X3/4X1	10	60	035	33.77
4101-120	1X1/2X1/2	10	120	035	36.39
4101-121	1X1/2X3/4	10	120	035	35.78
4101-122	1X1/2X1	10	120	035	27.52
4101-124	1X3/4X1/2	10	120	035	34.28
4101-125	1X3/4X3/4	10	120	035	18.56
4101-126	1X3/4X1	10	120	035	25.73
4101-130	1X1X1/2	10	120	035	17.39
4101-131	1X1X3/4	10	120	035	16.59
4101-138	1-1/4X1/2X1/2	10	80	035	45.34
4101-139	1-1/4X1/2X3/4	10	80	035	45.34
4101-142	1-1/4X1/2X1-1/4	10	80	035	40.16
4101-146	1-1/4X3/4X1/2	10	80	035	45.34
4101-147	1-1/4X3/4X3/4	10	80	035	45.34
4101-148	1-1/4X3/4X1	10	80	035	45.34
4101-149	1-1/4X3/4X1-1/4	10	80	035	45.34
4101-156	1-1/4X1X1/2	10	80	035	45.34
4101-157	1-1/4X1X3/4	10	80	035	45.34
4101-158	1-1/4X1X1	10	80	035	45.34
4101-159	1-1/4X1X1-1/4	10	80	035	40.16
4101-166	1-1/4X1-1/4X1/2	10	120	035	41.37
4101-167	1-1/4X1-1/4X3/4	10	80	035	41.37
4101-168	1-1/4X1	10	40	035	37.75
4101-169	1-1/4X1-1/4X1-1/2	5	40	035	56.35
4101-173	1-1/2X1/2X1/2	5	40	035	56.35
4101-174	1-1/2X1/2X3/4	5	40	035	56.35

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

REDUCING TEE (continued)

Socket x Socket x Socket

4101-175	1-1/2X1/2X1	5	40	035	56.35
4101-176	1-1/2X1/2X1-1/4	5	40	035	56.35
4101-177	1-1/2X1/2X1-1/2	5	40	035	40.16
4101-182	1-1/2X3/4X1/2	5	40	035	56.35
4101-184	1-1/2X3/4X3/4	5	40	035	56.35
4101-185	1-1/2X3/4X1	5	40	035	56.35
4101-186	1-1/2X3/4X1-1/4	5	40	035	56.35
4101-188	1-1/2X3/4X1-1/2	5	40	035	40.16
4101-193	1-1/2X1X1/2	5	40	035	56.35
4101-194	1-1/2X1X3/4	5	40	035	56.35
4101-195	1-1/2X1X1	5	40	035	37.75
4101-196	1-1/2X1X1-1/4	5	40	035	53.52
4101-197	1-1/2X1X1-1/2	5	40	035	40.16
4101-199	1-1/2X1-1/4X1/2	5	40	035	56.35
4101-201	1-1/2X1-1/4X3/4	5	40	035	56.35
4101-202	1-1/2X1-1/4X1	5	40	035	56.35
4101-203	1-1/2X1-1/4X1-1/4	5	40	035	56.35
4101-204	1-1/2X1-1/4X1-1/2	5	40	035	40.16
4101-209	1-1/2X1-1/2X1/2	5	30	035	40.16
4101-210	1-1/2X1-1/2X3/4	5	30	035	41.24
4101-211	1-1/2X1	10	30	035	56.35
4101-212	1-1/2X1-1/2X1-1/4	5	40	035	40.16
4101-213	1-1/2X1-1/2X2	5	0	035	99.16
4101-216	2X1/2X1/2	5	0	035	99.16
4101-217	2X1/2X3/4	5	0	035	99.16
4101-218	2X1/2X1	5	0	035	99.16
4101-219	2X1/2X1-1/4	5	0	035	99.16
4101-220	2X1/2X1-1/2	5	0	035	99.16
4101-221	2X1/2X2	5	0	035	79.19
4101-222	2X3/4X1/2	5	0	035	99.16
4101-223	2X3/4X3/4	5	0	035	99.16
4101-224	2X3/4X1	5	0	035	99.16
4101-225	2X3/4X1-1/4	5	0	035	99.16
4101-226	2X3/4X1-1/2	5	0	035	99.16
4101-227	2X3/4X2	5	0	035	79.19
4101-228	2X1X1/2	5	0	035	99.16
4101-229	2X1X3/4	5	0	035	99.16
4101-230	2X1X1	5	0	035	99.16
4101-231	2X1X1-1/4	5	0	035	99.16
4101-232	2X1X1-1/2	5	0	035	99.16
4101-233	2X1X2	5	0	035	79.19
4101-234	2X1-1/4X1/2	5	0	035	99.16
4101-235	2X1-1/4X3/4	5	0	035	99.16
4101-236	2X1-1/4X1	5	0	035	99.16
4101-237	2X1-1/2X1/2	5	0	035	99.16
4101-238	2X1-1/2X3/4	5	0	035	99.16
4101-239	2X1-1/2X1	5	0	035	99.16
4101-240	2X1-1/2X1-1/4	5	0	035	99.16
4101-241	2X1-1/2X1-1/2	5	0	035	99.16
4101-242	2X1-1/4X1-1/4	5	0	035	99.16
4101-243	2X1-1/4X1-1/2	5	0	035	99.16
4101-244	2X1-1/4X2	5	0	035	79.19
4101-247	2X2X1/2	10	0	035	58.49



**CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves & Pipe**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

REDUCING TEE (continued)

Socket x Socket x Socket

4101-248*	2X2X3/4	5	40	035	52.37
4101-249	2X1	5	15	035	49.62
4101-250*	2X2X1-1/4	5	0	035	49.62
4101-251	2X2X1-1/2	5	15	035	52.95
4101-257*	2X1-1/2X2	5	0	035	52.95

* Outlet sized with bushing.

90° ELL

Socket x Socket



4106-005	1/2	25	600	035	1.21
4106-007	3/4	25	300	035	2.00
4106-010	1	10	150	035	5.84
4106-012	1-1/4	10	80	035	11.63
4106-015	1-1/2	10	80	035	20.99
4106-020	2	5	30	035	40.25

REDUCING 90° ELL

Socket x Socket



4106-101	3/4X1/2	25	300	035	4.21
4106-130*	1X1/2	25	200	035	14.81
4106-131*	1X3/4	25	200	035	14.81
4106-167*	1-1/4X3/4	10	80	035	22.80
4106-168*	1-1/4X1	10	80	035	22.80
4106-209*	1-1/2X1/2	10	0	035	31.58
4106-210*	1-1/2X3/4	10	0	035	31.58
4106-211*	1-1/2X1	10	0	035	31.58
4106-212*	1-1/2X1-1/4	10	0	035	31.58
4106-247*	2X1/2	5	30	035	70.16
4106-248*	2X3/4	5	30	035	70.16
4106-249*	2X1	5	30	035	70.16
4106-250*	2X1-1/4	5	30	035	70.16
4106-251*	2X1-1/2	5	30	035	70.16

* Outlet sized with bushing.

SPECIAL REINFORCED 90° ELL

Socket x SR Fipt - Stainless Steel Collar



4107-005SR	1/2	50	300	035	9.01
------------	-----	----	-----	-----	------

ZINC DROP EAR REINFORCED CTS 90° ELL

(One Piece Unit)

Socket x SR Fipt - Zinc Collar



DEZ4107-005SR	1/2	10	150	035	20.26
---------------	-----	----	-----	-----	-------

DROP EAR 90° ELL (Fitting with Bracket)

Socket x Socket



DE4106-005	1/2	25	150	035	3.62
------------	-----	----	-----	-----	------

DROP EAR BRACKET ONLY

For 4101-005 and 4106-005



DES-005	1/2	800	0	035	6.17
---------	-----	-----	---	-----	------

DROP EAR SPECIAL REINFORCED 90° ELL

(Fitting Plus Bracket)

Socket x SR Fipt - Stainless Steel Collar



DE4107-005SR	1/2	10	200	035	13.93
--------------	-----	----	-----	-----	-------

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

DROP EAR BRACKET ONLY

For 4107-005SR



DET-005	1/2	400	0	035	6.17
---------	-----	-----	---	-----	------

90° STREET ELL

Spigot x Socket



4109-005	1/2	25	500	035	1.43
4109-007	3/4	25	300	035	2.24
4109-010	1	10	100	035	10.25

45° ELL

Socket x Socket



4117-005	1/2	25	500	035	1.54
4117-007	3/4	25	300	035	2.66
4117-010	1	10	100	035	6.77
4117-012	1-1/4	10	120	035	14.34
4117-015	1-1/2	10	80	035	20.78
4117-020	2	10	0	035	43.51

45° STREET ELL

Spigot x Socket



4127-005	1/2	25	600	035	3.26
4127-007	3/4	25	400	035	4.37
4127-010	1	10	150	035	12.56

COUPLING

Socket x Socket



4129-005	1/2	25	600	035	1.00
4129-007	3/4	25	300	035	1.32
4129-010	1	10	250	035	5.94
4129-012	1-1/4	10	120	035	7.67
4129-015	1-1/2	10	120	035	10.84
4129-020	2	10	0	035	20.64

REDUCER COUPLING

Socket x Socket



4129-101	3/4X1/2	25	300	035	2.12
4129-130	1X1/2	25	150	035	12.52
4129-131	1X3/4	25	150	035	6.78
4129-166*	1-1/4X1/2	10	120	035	15.69
4129-167*	1-1/4X3/4	10	120	035	15.69
4129-168*	1-1/4X1	10	120	035	22.33
4129-209*	1-1/2X1/2	10	80	035	21.28
4129-210*	1-1/2X3/4	10	60	035	21.28
4129-211*	1-1/2X1	10	60	035	21.28
4129-212*	1-1/2X1-1/4	10	80	035	21.28
4129-247*	2X1/2	10	0	035	46.09
4129-248*	2X3/4	10	0	035	46.09
4129-249	2X1	10	0	035	46.09
4129-250*	2X1-1/4	10	0	035	46.09
4129-251*	2X1-1/2	10	0	035	46.09

* Outlet sized with bushing.

FEMALE ADAPTER with Gasket

Socket x NPSC



For Cold Water Service Only

4135-005OR	1/2	25	200	035	4.71
4135-007OR	3/4	25	300	035	6.68



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

FEMALE ADAPTER with Gasket (continued)

Socket x NPSC

4135-010OR	1	5	100	035	7.62
------------	---	---	-----	-----	------

**GASKET SEALED BRASS THREAD
TRANSITION FEMALE ADAPTER**

Socket x Gasket FPT - Use NO Thread Sealant



NSF Certified Lead Free

4135-005BRG	1/2	25	150	035	40.21
4135-007BRG	3/4	25	150	035	44.28
4135-010BRG	1	15	90	035	132.09
4135-012BRG	1-1/4	15	60	035	250.97
4135-015BRG	1-1/2	10	40	035	327.12
4135-020BRG	2	8	32	035	480.95

**GASKET SEALED BRASS THREAD
TRANSITION REDUCING FEMALE ADAPTER**

Socket x Gasket FPT - Use NO Thread Sealant



NSF Certified Lead Free

4135-101BRG	3/4X1/2	25	150	035	43.77
4135-130BRG	1X1/2	50	0	035	69.15

SPECIAL REINFORCED FEMALE ADAPTER

Socket x SR Fipt - Stainless Steel Collar



4135-005SR	1/2	25	200	035	6.96
4135-007SR	3/4	25	300	035	7.65
4135-010SR	1	5	100	035	9.71

SPECIAL REINFORCED REDUCING FEMALE ADAPTER

Socket x SR Fipt - Stainless Steel Collar



4135-131SR	1X3/4	25	150	035	15.28
------------	-------	----	-----	-----	-------

MALE ADAPTER

Mipt x Socket



For Cold Water Service Only

4136-005	1/2	25	600	035	1.26
4136-007	3/4	25	300	035	2.15
4136-010	1	10	250	035	10.16
4136-012	1-1/4	25	200	035	15.74
4136-015	1-1/2	10	80	035	19.41
4136-020	2	10	80	035	32.00

REDUCING MALE ADAPTER

Mipt x Socket



For Cold Water Service Only

4136-074	1/2X3/4	25	600	035	4.60
4136-101	3/4X1/2	25	600	035	4.93

MALE ADAPTER

Mipt x Spigot



For Cold Water Service Only

4161-005	1/2	50	700	035	3.91
----------	-----	----	-----	-----	------

**REINFORCED MALE ADAPTER (Internal
Stainless Steel Reinforced)**

R Mipt x Socket - Stainless Steel Sleeve




4136-005R	1/2	25	300	035	8.93
4136-007R	3/4	25	300	035	9.93
4136-010R	1	10	120	035	14.79

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

**TRANSITION MALE ADAPTER w/BRASS
THREAD**

Brass Mipt x Socket


NSF Certified Lead Free



4136-005BR	1/2	60	360	035	40.21
4136-007BR	3/4	40	160	035	44.28
4136-010BR	1	10	60	035	132.09
4136-012BR	1-1/4	10	60	035	162.92
4136-015BR	1-1/2	10	40	035	215.06
4136-020BR	2	8	32	035	357.49

REDUCER BUSHING


Spigot x Socket



4137-101	3/4X1/2	25	600	035	1.51
4137-130	1X1/2	10	300	035	4.95
4137-131	1X3/4	10	400	035	4.95
4137-166	1-1/4X1/2	10	120	035	6.86
4137-167	1-1/4X3/4	10	300	035	6.42
4137-168	1-1/4X1	10	300	035	5.61
4137-209	1-1/2X1/2	25	100	035	8.07
4137-210	1-1/2X3/4	25	100	035	8.07
4137-211	1-1/2X1	10	120	035	7.92
4137-212	1-1/2X1-1/4	10	200	035	7.92
4137-247	2X1/2	10	60	035	19.16
4137-248	2X3/4	10	60	035	17.88
4137-249	2X1	10	60	035	17.88
4137-250	2X1-1/4	10	120	035	19.16
4137-251	2X1-1/2	10	120	035	17.88

TRANSITION BUSHING

IPS Spigot x CTS Socket



4140-005	1/2	10	600	035	6.40
4140-007	3/4	10	600	035	6.68
4140-010	1	10	400	035	7.38
4140-012	1-1/4	10	60	035	9.14
4140-015	1-1/2	10	60	035	11.52
4140-020	2	10	60	035	12.56

TRANSITION COUPLING

IPS Socket x CTS Socket




4141-007	3/4	25	300	035	4.36
4141-010	1	10	150	035	7.69

**CAP
Socket**



4147-005	1/2	25	600	035	1.09
4147-007	3/4	25	300	035	1.39
4147-010	1	10	400	035	5.07
4147-012	1-1/4	10	120	035	6.97
4147-015	1-1/2	10	120	035	10.72
4147-020	2	10	80	035	21.63

**CTS Union
Socket with EPDM O-ring Seal**



100 psi Maximum Internal Pressure @ 180°F (82°C)

4197-005	1/2	25	150	035	14.25
4197-007	3/4	10	60	035	21.69
4197-010	1	10	60	035	28.00



**CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves & Pipe**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

1/4-Turn Angle Supply Stop

Socket x NPT



100 psi @ 180°F (82°C)

1/2" & 3/8" Male Thread for Connection to Female Flexible Supply Line

7722-005	1/2	50	400	217	16.43
7722-073	1/2X3/8	50	400	217	16.43

1/4-Turn Angle Supply Stop

SR FPT x NPT



100 psi @ 180°F (82°C)

1/2" & 3/8" Male Thread for Connection to Female Flexible Supply Line

7721-005SR	1/2	50	400	217	40.69
7721-073SR	1/2X3/8	50	400	217	40.69

CPVC CTS Ball Valves

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Socket with EPDM O-ring Seal

100 psi Maximum Internal Pressure @ 180°F (82°C)

1922-005	1/2	50	200	217	33.39
1922-007	3/4	25	0	217	39.47
1922-010	1	25	0	217	45.53
1922-012	1-1/4	20	0	217	70.68
1922-015	1-1/2	20	0	217	101.94
1922-020	2	8	0	217	130.59

For additional valve information, please refer to Spears® Technical Information part 2 This book.

CPVC CTS Pipe - SDR 11

10' Lengths, Price Per Foot



List Price Per Foot

CTS-005	1/2	500	0	034	.92
CTS-007	3/4	250	0	034	1.65
CTS-010	1	150	0	034	3.39
CTS-012	1-1/4	100	0	034	5.03
CTS-015	1-1/2	100	0	034	6.67
CTS-020	2	50	0	034	11.29


- Pipe sold in bag quantities only - no broken bags
- No return on Pipe
- Large orders may be shipped directly from Spears® manufacturing facility. Note: Multiple drops may be made on TL shipments. Contact Spears® Regional Distribution Center for requirements and drop-off charges.
- See Spears® Manufacturing Company Terms and Conditions of Sale for freight requirements.

CPVC CTS PIPE WEIGHTS:

- CTS-005 Weight per Foot .090 lbs; per Bag Weight 45 lbs.
- CTS-007 Weight per Foot .149 lbs; per Bag Weight 37.25 lbs.
- CTS-010 Weight per Foot .239 lbs; per Bag Weight 35.85 lbs.
- CTS-012 Weight per Foot .353 lbs; per Bag Weight 35.3 lbs.
- CTS-015 Weight per Foot .489 lbs; per Bag Weight 48.9 lbs.
- CTS-020 Weight per Foot .810 lbs; per Bag Weight 40.5 lbs.

CPVC CTS Pipe - SDR 11

20' Lengths, Price Per Foot



List Price Per Foot

CTS-005-20	1/2	1000	0	034	.92
CTS-007-20	3/4	500	0	034	1.65
CTS-010-20	1	300	0	034	3.39
CTS-012-20	1-1/4	200	0	034	5.03
CTS-015-20	1-1/2	200	0	034	6.67
CTS-020-20	2	100	0	034	11.29

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

CPVC CTS Pipe - SDR 11 (continued)

20' Lengths, Price Per Foot

- Pipe sold in bag quantities only - no broken bags
- No return on Pipe
- Large orders may be shipped directly from Spears® manufacturing facility. Note: Multiple drops may be made on TL shipments. Contact Spears® Regional Distribution Center for requirements and drop-off charges.
- See Spears® Manufacturing Company Terms and Conditions of Sale for freight requirements.

CPVC CTS PIPE WEIGHTS:

- CTS-005 Weight per Foot .090 lbs; per Bag Weight 90 lbs.
- CTS-007 Weight per Foot .149 lbs; per Bag Weight 74.5 lbs.
- CTS-010 Weight per Foot .239 lbs; per Bag Weight 71.7 lbs.
- CTS-012 Weight per Foot .353 lbs; per Bag Weight 70.6 lbs.
- CTS-015 Weight per Foot .489 lbs; per Bag Weight 97.8 lbs.
- CTS-020 Weight per Foot .830 lbs; per Bag Weight 83 lbs.

CPVC CTS Coiled Pipe - SDR 11

100 ft. Coil, Price Per Foot



List Price Per Foot

CTS-005-100	1/2	100	0	034	1.08
CTS-007-100	3/4	100	0	034	1.96
CTS-010-100	1	100	0	034	3.86

- Pipe sold in coil quantities only - no broken coils
- No return on Coiled Pipe
- Large orders may be shipped directly from Spears® manufacturing facility. Note: Multiple drops may be made on TL shipments. Contact Spears® Regional Distribution Center for requirements and drop-off charges.
- See Spears® Manufacturing Company Terms and Conditions of Sale for freight requirements.

CPVC CTS COILED PIPE WEIGHTS:

- CTS-005-100 Weight per Foot .090 lbs; per Coil Weight 9 lbs.
- CTS-007-100 Weight per Foot .149 lbs; per Coil Weight 14.9 lbs.
- CTS-010-100 Weight per Foot .239 lbs; per Coil Weight 23.9 lbs.

WARNING:

Banded coils will expand when opened. Exercise caution to avoid injury during banding removal.

CTS TUBING STRAPS

Std Pk Bag of 25 For Anchoring CTS Pipe



Sold in Full Bag Quantity Only

556A	1/2	25	500	901	.94
556B	3/4	25	500	901	.94

CTS TUBE TALON with NAIL

Std Pk Bag Quantities as Specified. For Anchoring CTS Pipe



Sold in Full Bag Quantity Only

555A	1/2	100	1000	901	1.04
555B	3/4	100	1000	901	1.58
555C	1	50	500	901	4.44

EverTUFF® CTS One Step CPVC Solvent Cement



CTS5-005	1/4 Pint	24	0	701	9.01
CTS5-010	1/2 Pint	24	0	701	14.34
CTS5-020	Pint	12	0	701	23.23
CTS5-030	Quart	12	0	701	40.42

Cap Daubers



DHP-38	3/8" for 1/2 Pint	50	400	710	1.23
DHP-50	1/2" for 1/2 Pint	50	400	710	1.23
DHP-75	3/4" for 1/2 Pint	50	0	710	1.31

**CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves & Pipe**



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Cap Daubers (continued)

DP-50	1/2" for Pint	50	0	710	1.23
DP-75	3/4" for Pint	50	0	710	1.31
DP-125	1-1/4" for Pint	50	0	710	1.58
DQ-50	1/2" for Quart	50	0	710	1.23
DQ-75	3/4" for Quart	50	0	710	1.23
DQ-125	1-1/4" for Quart	50	0	710	1.58

3/8" Diameter for pipe sizes to 3/4"
1/2" Diameter for pipe sizes to 1"
3/4" Diameter for pipe size to 1-1/2"
1-1/4" Diameter for pipe size 1-1/2" to 3"

Can-Mate Daubers

Adjustable Plastic Applicator with Telescoping Stem for use with Standard 1/2 Pint, Pint and Quart Cans



CM-50	1/2"	50	0	710	5.26
CM-75	3/4"	50	0	710	5.26
CM-150	1-1/4"	50	0	710	5.26

1/2" Diameter for pipe sizes to 1"
3/4" Diameter for pipe size to 1-1/2"
1-1/4" Diameter for pipe size 1-1/2" to 3"

Deburring Tool

Cone Type for pipe from 1/2" through 2"



DEB-2	1/2 to 2 Pipe	1	6	710	97.71
-------	----------------------	---	---	-----	-------