



Schedule 80 PVC Industrial Products & Accessories Globe Valves & Needle Valves

Globe Valves



Pressure Rating @ 73°F (23°C), Water
2-1/2" - 6" 150 psi
Maximum Service Temperature
PVC = 140°F (60°C)
Temperature/Pressure De-ratings Apply
All Valves Assembled with Silicone-Free,
Water Soluble Lubricant
Suitable for Vacuum Service

Internal Repair Kit includes 1-Bonnet O-ring along with a factory assembled (required) internal component replacement unit consisting of Bonnet assembled with Stem/O-rings, Seat & Seal Carrier components. Install in valve using existing valve Bolts/Nuts/Washers, and Handle/Nut.

PVC Flanged Ends

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
2-1/2	6013-025 608.27	6023-025 643.73	6033-025 693.48	1	0	620
3	6013-030 697.26	6023-030 728.15	6033-030 810.33	1	0	620
4	6013-040 791.04	6023-040 945.64	6033-040 1039.07	1	0	620
6	6013-060 1216.55	6023-060 1454.71	6033-060 1483.69	1	0	620

PVC Internal Repair Kit

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
2-1/2	GL-BRK-025 202.35	GL-ERK-025 489.42	GL-VRK-025 544.35	1	0	299
3	GL-BRK-030 225.51	GL-ERK-030 542.27	GL-VRK-030 604.42	1	0	299
4	GL-BRK-040 264.58	GL-ERK-040 635.91	GL-VRK-040 699.16	1	0	299
6	GL-BRK-060 576.49	GL-ERK-060 977.16	GL-VRK-060 997.16	1	0	299

Needle Valves



Pressure Rating @ 73°F (23°C), Water
PVC 235 psi
Maximum Service Temperature
PVC = 140°F (60°C)
Solid PTFE Stem Seals
No Elastomer or Lubricants used
Valves include Panel Mounting Nut

PVC Needle Valve

Size	Threaded	Socket	SR Threaded	Std Pk	Mstr Pk	Disc Code
------	----------	--------	-------------	--------	---------	-----------

Globe Pattern

1/4	5591-002 71.27	5592-002 71.27	---	1	18	218
3/8	5591-003 71.27	5592-003 71.27	---	1	18	218
1/2	5591-005 79.11	5592-005 79.11	5591-005SR 81.23	1	18	218

Angle Pattern

1/4	5691-002 71.27	5692-002 71.27	---	1	18	218
3/8	5691-003 71.27	5692-003 71.27	---	1	18	218
1/2	5691-005 79.11	5692-005 79.11	5691-005SR 81.23	1	18	218